

# INDECAR

MAQUINAS AGRICOLAS

DESMALEZADORA PARA 3 PUNTOS  
3-POINT HITCH ROTARY CUTTER

→ ¡Ofrecemos los mejores precios del mercado. Consulte!



→ **DT 1.5**



📌 **DISEÑADA ESPECIALMENTE PARA TRABAJOS EXTREMOS**  
ESPECIALLY DESIGNED FOR HEAVY DUTY

## → CARACTERÍSTICAS TÉCNICAS

### TECHNICAL CHARACTERISTICS

**INDECAR**  
MAQUINAS AGRICOLAS



Rueda de apoyo trasera de hierro,  
altura regulable

*Height adjustable tail support wheel  
made of iron*

Plataforma plegada en chapa de  
5mm de espesor

*Platform folded in 5 mm thick  
sheet metal*



Patines regulables y cambiables  
con tres posiciones de altura

*Adjustable and removable skid shoes with  
three height positions.*

Doble cuchilla de corte, oscilante  
de acero especial

*Dual oscillating cutting blades made of special steel*



● Medidas disponibles desde  
1,5 a 5,5 mts. de ancho de corte

*Range of cutting width available from 1.5 to 5.5 m*



DESMALEZADORA  
PARA 3 PUNTOS

3-POINT HITCH ROTARY CUTTER

**DT 1.5**



Caja de transmisión Oripion reforzada en  
baño de aceite

*Reinforced Oripion gearbox, lubricated  
in oil bath.*

Pintura (fondo + color) poliuretano  
Polyurethane paint: varnish + color



Sistema de cardan a 540 RPM  
Cardan system operating range: 540 rpm

Barra cardánica con zafe fusible a resortes  
PTO shaft with a spring-loaded fusible plug  
as a safety device

