



STEIGER® 785 QUADTRAC®

The iconic Steiger® series is back with more power than ever. Purposefully designed for performance and unparalleled productivity, the Steiger 785 Quadtrac® is Case IH's highest horsepower tractor yet. Including subscription-free, integrated technology, the newest Steiger model offers increased horsepower by almost ten percent over the Steiger 715 Quadtrac, making this the perfect partner for farmers who are aiming to get even more done on their operations.

Benefits For Farmers

- **Engineered Power:** Handle larger implements or the same implements even faster. This system delivers a powerful workhorse tractor without reducing speed or adding weight.
- **Designed for an Optimal Ride:** Enjoy a more comfortable experience, in and out of the field, with an optional Quadtrac heavy-duty suspended undercarriage. The optional suspended undercarriage provides a smoother ride and more power to the ground.
- **Simplified Tech and Connectivity Included:** Access subscription-free, integrated technology to meet the unique needs of your operation. Regardless of who is in the cab, boost performance with easy-to-view data and easy-to-use automation.
- **Lifetime Value:** Optimize productivity and maximize the value of the Steiger 785 Quadtrac with 3-year/2,000-hour warranty and a simplified SCR-only emission system that keeps engine design simple and allows the engine to focus on producing power while emissions are treated after the engine system.

What It Offers

- The Steiger 785 Quadtrac model is the **highest horsepower tractor yet** (785 rated/853 peak @ 1900 erpm) from Case IH, offering an impressive **40 percent torque rise**, allowing operators to pull the same implements faster or larger implements without a reduction in speed.

STEIGER 785 QUADTRAC



- The **heavy-duty suspended undercarriage** option reduces soil compaction while offering improved ride quality, superior traction and flotation.
- Operators will maintain **easy access to routine maintenance** items with toolless removable debris shields, electrically-actuated easy open hood, engine oil dipstick access door, air filter access panel and clear undercarriage fluid inspection caps.
- The Steiger 785 Quadtrac comes with an **expansive fuel capacity of 520 gallons** for more time in the field between fueling.
- The Steiger 785 Quadtrac model includes **three different lighting packages** that create **greater visibility** for operators.
- The Steiger 785 Quadtrac was built with a longer track design and provides **increased traction**, a **larger footprint** and maneuverability.
- Owners and operators can seamlessly **connect, view and manage** their agronomic and machine data through FieldOps™, increasing overall operational efficiencies.
- Two precision **Technology Packages** are available for the Steiger 785 Quadtrac, with purposefully chosen technology features to simplify ordering and ensure operations are equipped with the tech suite they need for their operation--all without subscriptions (see table below for details).

STEIGER TRACTORS TECH PACKAGES

	Display	Telematics	ISOBUS	Guidance and Machine Coordination		Accuracy	Additional Activations Included
Core	Single Pro 1200, or Dual Pro 1200s	Connectivity Included	Class 2	AccuTurn Pro	AccuSync	Vector Pro Receiver – AFS 3 (3 yr) or Vector Pro Receiver – AFS 1 (3 yr) (optional)	Multiswath Line Splitting Multiproduct Control Advanced Section Control Active Implement Guidance
Advanced	Single Pro 1200, or Dual Pro 1200s	Connectivity Included	Class 2/3	AccuTurn Pro	AccuSync	Vector Pro Receiver – High w/ NTRIP (3 yr)	

CASE IH

BUILT BY FARMERS.

STEIGER 785 QUADTRAC



Model	Steiger 785 Quadtrac
POWER	
Engine Type	Tier 4 B/Final - Stage V with TST two-stage turbocharger
Cylinders/Valves/Displacement	6 cyl./24/16L (970 cu. in.)
Engine HP ¹	785
Maximum Engine HP ²	853
PTO HP ³	537
TRANSMISSION/PTO	
Standard	PowerDrive full-powershift 16F/2R with 16 Hi (26.5 mph/42.6 kph)
AXLES	
Wheelbase	154 in. (3 912 mm)
HYDRAULICS/HITCH	
Rear Remotes (Standard/Optional)	4/up to 8
Hydraulic Pump - PowerDrive (Standard)	57 gpm (216 L/min)
Total Tractor Hydraulic Flow with Parallel/TwinFlow Pumps	113 gpm (428 L/min)
Hitch Lift Capacity	22,250 lb. (98.97 kN)
CAPACITIES	
Fuel Tank	520 gal. (1 968 L)
Diesel Exhaust Fluid (DEF) Tank	85 gal. (322 L)
DIMENSIONS & WEIGHTS	
Drawbar (Standard/Option 1/Option 2)	Cat 5: 15,000 lb. (6 804 kg)
Base Weight/Maximum Weight (GVW)	61,200 lb. (27 760 kg)/72,000 lb. (32 659 kg)

¹Rated 2,100 engine rpm ISO per ECE R120 (CV) ²1,900 engine rpm ISO per ECE R120 (CV) ³1,000 PTO rpm ISO per ECE R120 (CV) - Power boost available during mobile PTO/hydraulics/transport operation